



物料精准处理系统专家

Expert in precise material handling systems

设备特点 Equipment features

节能:	是传统后烘能耗节能约 30%~50%	Energy saving: saves about 30%~50% of the energy consumption of		
		traditional post-drying, the difference mainly comes from the layout and		
		scale;		
高效:	与挤出机产线直连,可以实现连续生产	High efficiency: directly connected to the extruder production line,		
		continuous production can be achieved;		
质量:	全自动管控,物料受热均匀,温度偏差小	Quality: Fully automatic control, materials are heated evenly, and		
		temperature deviation is small;		
清洁:	内部结构简单,易清洁	Cleaning: The internal structure is simple and easy to clean;		
安全:	保护连锁,防止结块	Safety: protect the chain and prevent abnormalities such as build up		

技术参数 Technical parameters

产品牌号 Product Brand	产能 (公斤/小时) Capacity (kg/hour)	气味等级 Odor level	停留时间 Residence time	单吨能耗 Energy consumption per ton	测试标准 Test Standards	
PM40	1300	3.0	6Н	≤140KWH/T	大众PV3900	
PM20	1600	3.0	5H	≤120KWH/T		
PM20	1600	2.5+	5H	≤150KWH/T	XXPV3900	
PM20	1800	3.0	5.5H	≤100KWH/T		

应用领域 Application Areas

主要应用于聚丙烯改性塑料产品,尤其是高端汽车低气味内 饰产品。

Mainly used in polypropylene modified plastic products, especially high-end automotive low-odor interior products.







电话: +86 0510-68228600 邮箱: info@lingood.cn

TEL. +86 0510-68228600 EMAIL. info@lingood.cn 地址: 江苏省无锡市新吴区珠江路95-2号 网址: https://www.lingood.com.cn/

ADD. No.95-2, Zhujiang Rd, Xinwu, Wuxi, Jiangsu WEB. https://www.lingoodtech.com/

详细信息请扫码关注"灵鸽科技"官方微信公众号







官方视频号

官方微信号

官方抖音号